

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 58-148507  
 (43)Date of publication of application : 03.09.1983

(51)Int.CI.

H03F 3/72

(21)Application number : 57-031067  
 (22)Date of filing : 28.02.1982


(71)Applicant : YOKOGAWA HEWLETT PACKARD LTD  
 (72)Inventor : TAKAGI SHUN

## (54) COMPOSITE CONTROLLING AMPLIFIER

## (57)Abstract:

**PURPOSE:** To hold a terminal voltage of a load constantly, by controlling an amplifier to be controlled with a specific controlling amplifier.

**CONSTITUTION:** When an operational amplifier 4 is controlled with a controlling amplifier 2, a saturation preventing current  $I_{S1}$  flows to a controlling amplifier 1' in this state. A prescribed relation exists among the  $I_{S1}$ , an input voltage  $V_1$  of the amplifier 1' and an output voltage  $V_0$ . Thus, when a switch SW2 is opened and the control of an operational amplifier 4 with the amplifier 2 is blocked, the control of the controlling amplifier 1' is realized quickly. No spike voltage due to the controlling amplifier switching is generated. Since the operational amplifier 4 is controlled with the amplifier 1' exclusively, the output voltage  $V_0$  is unchanged even if voltages  $V_M$ ,  $V_2$ , and  $V_3$  are changed.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C) 1998,2003 Japan Patent Office

BEST AVAILABLE COPY